

**Strapping pallets
easy, fast & effortless**



Strapper
**Horizontal
Semiautomatic**

2820

Machine for horizontal pallet strapping. It can be moved to where the pallet is.

Easy to move to where it is being palletized.
Effortlessly manually adjustable strapping height.
Allows strapping from 135 mm ground level up to 2400 mm.
Adjustable tension by electromagnetic clutch. Capable of giving tensions between 3 and 80 Kg.
Wheel release lever.
Quick and easy strap coil change.
Strapping head made of aluminium.
Hardened tension rollers for greater resistance.
Includes a compartment to carry corner pieces.
Ergonomic handle.
Available in 3 different power supply versions.



OPTIONS:

Plug version.
Battery version.
Replaceable batteries version.
Battery changing car.



Anyone can strap pallets with the same tension at all strapping heights with this machine.

This strapping machine allows strapping on the wooden block and also goes up to 2400 mm to strap export pallets.

GENERAL CHARACTERISTICS

REQUIRED VOLTAGE: 220 V / 380 V · 50 / 60 Hz · Monophase

POWER: 0,5 Kw

PRODUCTION: 1 palet / min (3 straps)

MACHINE DIMENSIONS

900 (W) x 1116 (L) x 2939 (H) mm

TECHNICAL SPECIFICATIONS

STRAP WIDTH: 11 - 12 mm

WELDING: Adjustable
Electrical heating.

STRAP THICKNESS: 0,5 - 0,7 mm



Edition 06/22 - The manufacturer reserves the right to make changes without prior notice.